

View Online at <https://aerobasegroup.com/nsn/5305-01-270-8855>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.067 inches and 1.250 inches

Fastener Length:

Between 1.210 inches and 1.250 inches

Head Style:

Fillister

Head Diameter:

Between 0.368 inches and 0.375 inches

Head Height:

Between 0.550 inches and 0.562 inches

Locking Feature:

Pellet threads or strip threads or patch threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.3125 inches and 0.3160 inches

Thread Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Surface Finish:

63.0 microinches grip

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0