

View Online at <https://aerobasegroup.com/nsn/5305-01-270-8855>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.067 inches and 1.250 inches

**Fastener Length:**

Between 1.210 inches and 1.250 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.368 inches and 0.375 inches

**Head Height:**

Between 0.550 inches and 0.562 inches

**Locking Feature:**

Pellet threads or strip threads or patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.3125 inches and 0.3160 inches

**Thread Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell b

**Surface Finish:**

63.0 microinches grip

**Material:**

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0