

View Online at <https://aerobasegroup.com/nsn/5305-01-270-8917>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.335 inches and 1.500 inches

**Fastener Length:**

Between 1.460 inches and 1.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.550 inches and 0.562 inches

**Head Height:**

Between 0.368 inches and 0.375 inches

**Hole Diameter:**

Between 0.061 inches and 0.067 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

Between 0.312 inches and 0.316 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Hardness Rating:**

80.0 rockwell c

**Minimum Yield Strength:**

30000 pounds per square inch

**Hole Configuration Style:**

Round internal hexagon

**Special Features:**

Head may or may not be knurled at manu. Option type of knurling optional and may not exceed head dia.

**Material:**

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0