NSN 5305-01-271-4338



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-271-4338 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.638 inches and 1.750 inches **Fastener Length:** Between 1.688 inches and 1.750 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Steel comp 301 or steel comp 302 or steel comp 303 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 323 or steel comp 324 or steel comp 347 or steel comp 348 or steel comp 385 or steel comp 302b or steel comp 384 or steel comp 303se **Screw Material Specification:** 66 assn standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig:

No

Demilitarization: