## NSN 5305-01-271-8396

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-271-8396 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.296 inches and 0.328 inches **Fastener Length:** Between 0.546 inches and 0.578 inches **Head Style:** Fillister **Head Diameter:** Between 0.280 inches and 0.320 inches **Head Height:** Between 0.720 inches and 0.770 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.084 inches and 0.096 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Min. Tensile strength 70000 on 300 series only Material: Steel comp 302 spring or steel comp 304 spring or steel comp 305 spring or steel comp 310 spring or steel comp 316 spring or steel comp 321 spring or steel comp 347 spring or steel comp 410 spring or steel comp 420 spring or steel comp 430 spring **Material Specification:** Qq-w-423 federal specification single material response spring **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

Fiig:

A003b0