NSN 5305-01-272-0675

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-272-0675 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.250 inches **Fastener Length:** 0.812 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.421 inches and 0.453 inches Point Length: Between 0.240 inches and 0.250 inches **Point Diameter:** Between 0.115 inches and 0.130 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.400 inches and 0.420 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 85.0 degrees and 95.0 degrees **Special Features:** Straight knurl Material: Steel comp 303 **Material Specification:** Aisi assn standard single material response

Surface Treatment:

Passivate

NSN 5305-01-272-0675

Externally Relieved Body Screw - Page 2 of 2



Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0