NSN 5305-01-272-1331

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-272-1331

O a
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.542 inches and 0.644 inches
Fastener Length:
Between 0.719 inches and 0.750 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.442 inches and 0.507 inches
Locking Feature:
Patch threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
24.0 rockwell c fastener and 35.0 rockwell c fastener
Minimum Yield Strength:
85000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Plastic locking feature
Material Specification:
Mil-f-18240 military specification single material response locking feature
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unjf
Specification Data:
80205-nas1189 professional/industrial association standard
Shelf Life:
N/

N/a

NSN 5305-01-272-1331

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-18240 spec.