

View Online at <https://aerobasegroup.com/nsn/5305-01-272-8304>

Thread Direction:

Right-hand

Thread Length:

Between 2.6 millimeters and 4.0 millimeters

Fastener Length:

Between 3.5 millimeters and 4.0 millimeters

Head Style:

Pan

Head Diameter:

Between 3.94 millimeters and 4.24 millimeters

Head Height:

Between 1.35 millimeters and 1.58 millimeters

Internal Drive Style:

Cross recess type 1

Thread Diameter:

2.2 millimeters

Min. Tensile Strength (psi):

80000 pounds per square inch

Thread Pitch In Millimeters:

0.45

External Thread Tolerance Class:

6g

Product Name:

Navy special project

Screw Material:

Steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 322 or steel comp 324 or steel comp 347 or steel comp 302 or steel comp 303 or steel comp 302b or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 384

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924, c14 military specification single treatment response

Color:

Black

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.