

View Online at <https://aerobasegroup.com/nsn/5305-01-272-9754>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.251 inches and 0.301 inches

Fastener Length:

Between 0.511 inches and 0.541 inches

Head Style:

Fillister

Head Diameter:

Between 0.265 inches and 0.270 inches

Head Height:

Between 0.088 inches and 0.102 inches

Hole Diameter:

Between 0.034 inches and 0.042 inches

Grip Diameter:

Between 0.1625 inches and 0.1635 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.164 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

24.0 rockwell c and 35.0 rockwell c

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Round perpendicular

Surface Finish:

32.0 microinches threads

Material:

Iron alloy 660

Material Specification:

Ams5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1122 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0