## NSN 5305-01-273-1626

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-273-1626 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 1.170 inches and 1.705 inches **Fastener Length:** Between 3.420 inches and 3.500 inches **Head Style:** Fillister extended washer **Head Diameter:** Between 1.107 inches and 1.125 inches **Head Height:** Between 0.920 inches and 0.930 inches **Extended Washer Diameter:** 1.312 inches **Extended Washer Thickness:** 0.180 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.750 inches Width Across Flats: Between 0.625 inches and 0.631 inches Thready Qty Per Inch (tpi): 10 **Special Features:** Under cut side of head, 0.056min. And 0.060max. Wide and 1.052min. And 1.060max. Dia. Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-273-1626

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0