

View Online at <https://aerobasegroup.com/nsn/5305-01-273-2269>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.341 inches and 0.391 inches

**Fastener Length:**

Between 0.663 inches and 0.693 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.338 inches and 0.381 inches

**Locking Feature:**

Patch threads

**Single Shear Strength:**

95000 pounds per square inch

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Plastic locking feature

**Material Specification:**

Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas7203 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0