

View Online at <https://aerobasegroup.com/nsn/5305-01-273-2271>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.407 inches and 0.688 inches

**Fastener Length:**

Between 0.678 inches and 0.698 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.105 inches and 0.120 inches

**Width Between Flats:**

Between 0.305 inches and 0.314 inches

**Point Length:**

0.100 inches

**Point Diameter:**

Between 0.142 inches and 0.147 inches

**Point Style:**

Chamfer dog

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.190 inches

**Width Across Flats:**

Between 0.1875 inches and 0.1895 inches

**Thready Qty Per Inch (tpi):**

32

**Point Chamfer Angle:**

45.0 degrees

**Special Features:**

2 external slots 0.044 in. Min 0.054 in. Maximum dia

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Surface Treatment:**

Chromate and cadmium

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0