NSN 5305-01-273-2271

Setscrew - Page 1 of 2

Thread Class:

Shelf Life:



View Online at https://aerobasegroup.com/nsn/5305-01-273-2271

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.407 inches and 0.688 inches
Fastener Length:
Between 0.678 inches and 0.698 inches
Head Style:
Hexagon
Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.314 inches
Point Length:
0.100 inches
Point Diameter:
Between 0.142 inches and 0.147 inches
Point Style:
Chamfer dog
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.1875 inches and 0.1895 inches
Thready Qty Per Inch (tpi):
32
Point Chamfer Angle:
45.0 degrees
Special Features:
2 external slots 0.044 in. Min 0.054 in. Maximum dia
Material:
Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel
comp 385
Surface Treatment:
Chromate and cadmium
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unf

NSN 5305-01-273-2271

Setscrew - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0