NSN 5305-01-273-2278

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-273-2278

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.750 inches
Fastener Length:
Between 2.190 inches and 2.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.937 inches
Head Height:
Between 0.616 inches and 0.625 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.625 inches
Width Across Flats:
Between 0.500 inches and 0.505 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Material Specification:
66 assn standard all material responses or astm a493 assn standard all material responses
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type 1 cl 2 federal specification single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-273-2278

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0