## NSN 5305-01-273-4382

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-273-4382



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.307 inches and 0.357 inches Fastener Length: Between 1.478 inches and 1.498 inches **Head Style:** Crowned hexagon **Head Height:** Between 0.157 inches and 0.172 inches Width Between Flats: Between 0.492 inches and 0.502 inches Locking Feature: Detent ball **Grip Diameter:** Between 0.3112 inches and 0.3117 inches **Shank Unthreaded Hole Diameter:** 0.076 inches and 0.086 inches **Internal Drive Style:** Slot **End Application:** Aircraft model sh-60b **Thread Diameter:** 0.312 inches Grip Length: Between 1.000 inches and 1.016 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 1.365 inches first hole and 1.385 inches first hole Surface Finish: 32.0 microinches bearing surface of head Material: Steel **Material Specification:** Ams5629 assn standard single material response Surface Treatment:

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

## NSN 5305-01-273-4382

Close Tolerance Screw - Page 2 of 2

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

