NSN 5305-01-273-6236

No Fiig: A003b0

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-273-6236 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.225 inches and 0.275 inches **Fastener Length:** Between 0.525 inches and 0.555 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.106 inches and 0.113 inches **First Diameter From Head:** 0.099 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.280 inches and 0.300 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**