## NSN 5305-01-273-6239

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-273-6239 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.445 inches and 0.495 inches **Fastener Length:** Between 6.205 inches and 6.235 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.597 inches and 0.612 inches **Head Height:** Between 0.176 inches and 0.188 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1218 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5305-01-273-6239

Machine Screw - Page 2 of 2



Fiig:

A500d0