3a

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-273-6241



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.657 inches and 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches Locking Feature: Pellet locking feature or strip locking feature **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 36.0 rockwell c fastener and 45.0 rockwell c fastener **Minimum Yield Strength:** 155000 pounds per square inch Material: Steel fastener Surface Treatment: Cadmium fastener and chromate fastener Surface Treatment Specification: Qq-p-416 type 2 cl 3 federal specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: Unit Of Measure:

N/a

32

NSN 5305-01-273-6241

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

