## NSN 5305-01-273-6241

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-273-6241 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.657 inches and 0.750 inches **Fastener Length:** Between 0.719 inches and 0.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Locking Feature:** Pellet locking feature or strip locking feature **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 36.0 rockwell c fastener and 45.0 rockwell c fastener Minimum Yield Strength: 155000 pounds per square inch Material: Steel fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response fastener **Thread Series Designator:** Unc

Shelf Life: N/a **Unit Of Measure:** 

## NSN 5305-01-273-6241

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0