## NSN 5305-01-273-6843

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-273-6843 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.210 inches **Fastener Length:** 0.840 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches Point Length: 0.080 inches **Point Diameter:** Between 0.115 inches and 0.125 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches **Second Diameter From Head:** Between 0.105 inches and 0.115 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.070 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.550 inches Point Style: Ball **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Stainless steel

Unc

**Thread Series Designator:** 

## NSN 5305-01-273-6843

Externally Relieved Body Screw - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0