

NSN 5305-01-274-0034 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-274-0034 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 4.766 inches and 5.000 inches **Fastener Length:** Between 4.920 inches and 5.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Hole Diameter:** Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.375 inches **Hole Quantity:** 

**Hole Type:** 

riole Type.

Drilled

Thready Qty Per Inch (tpi):

13

Min. Tensile Strength (psi):

180000 pounds per square inch

**Hardness Rating:** 

38.0 rockwell c and 45.0 rockwell c

**Hole Configuration Style:** 

Round internal hexagon

Surface Finish:

63.0 microinches bearing surface of head

Material:

Steel

**Surface Treatment:** 

Zinc and chromate

**Surface Treatment Specification:** 

Astm b633 type 2 cl 3 assn standard single treatment response

## NSN 5305-01-274-0034

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0