
## NSN 5305-01-274-0034

Socket Head Cap Screw - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 4.766 inches and 5.000 inches Fastener Length: Between 4.920 inches and 5.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches Hole Diameter: Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: 0.375 inches **Hole Quantity:** 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Hole Configuration Style: Round internal hexagon Surface Finish: 63.0 microinches bearing surface of head Material: Steel Surface Treatment: Zinc and chromate **Surface Treatment Specification:** 

Astm b633 type 2 cl 3 assn standard single treatment response

## NSN 5305-01-274-0034

Socket Head Cap Screw - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0