NSN 5305-01-274-2899

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-274-2899 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.789 inches and 0.890 inches **Fastener Length:** Between 0.860 inches and 0.890 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.2435 inches and 0.2500 inches **Head Height:** Between 0.244 inches and 0.250 inches **Locking Feature:** Pellet threads or strip threads or patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 80000 pounds per square inch **Hardness Rating:** 80.0 rockwell c Material: Steel comp 302 or steel comp 305 or steel comp 304 or steel comp 316 or steel comp 384 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 1 type

N/a

Shelf Life:

NSN 5305-01-274-2899

Socket Head Cap Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0