

View Online at <https://aerobasegroup.com/nsn/5305-01-274-2899>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.789 inches and 0.890 inches

Fastener Length:

Between 0.860 inches and 0.890 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.2435 inches and 0.2500 inches

Head Height:

Between 0.244 inches and 0.250 inches

Locking Feature:

Pellet threads or strip threads or patch threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.250 inches

Width Across Flats:

Between 0.1875 inches and 0.1900 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell c

Material:

Steel comp 302 or steel comp 305 or steel comp 304 or steel comp 316 or steel comp 384

Material Specification:

Astm a493 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0