NSN 5305-01-274-3244

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-274-3244

View Crimina at this particular and a second control of the contro
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.408 inches and 0.500 inches
Fastener Length:
Between 0.470 inches and 0.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Hole Diameter:
Between 0.033 inches and 0.039 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
0.109 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Hole Configuration Style:
Round internal hexagon
Surface Finish:
63.0 microinches bearing surface of head
Material:
Steel
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Astm b633 type 2 cl 3 assn standard single treatment response

NSN 5305-01-274-3244

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0