## NSN 5305-01-274-4479

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-274-4479

Thread Class:
3a
Thread Direction:
Right-hand
ŭ
Thread Length:  Between 1.849 inches and 2.000 inches
Fastener Length:
Between 1.960 inches and 2.000 inches
Head Style: Flat chamfer
Head Diameter:
Between 0.457 inches and 0.469 inches
Head Height:  Between 0.306 inches and 0.312 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.312 inches
Width Across Flats:
0.250 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Hole Configuration Style:
Round internal hexagon
Surface Finish:
63.0 microinches bearing surface of head
Material:
Steel
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Astm b633 type 2 cl 3 assn standard single treatment response
71 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 - 7 -

## NSN 5305-01-274-4479

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0