NSN 5305-01-274-5659

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-274-5659 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.298 inches and 0.348 inches **Fastener Length:** Between 0.746 inches and 0.776 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.428 inches and 0.448 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Unjf

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-01-274-5659

Close Tolerance Screw - Page 2 of 2



Spec	ifica	tion	Data:
------	-------	------	-------

80205-nas7803 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0