

View Online at <https://aerobasegroup.com/nsn/5305-01-274-6080>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.241 inches and 0.312 inches

Fastener Length:

Between 1.359 inches and 1.389 inches

Head Style:

Fillister countersunk

Head Diameter:

Between 0.389 inches and 0.394 inches

Head Height:

0.015 inches

Grip Diameter:

Between 0.2490 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Grip Length:

Between 1.052 inches and 1.072 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.238 inches first hole and 1.278 inches first hole

Special Features:

Color no. 37875 per fed-std-595

Color:

White head

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0