## NSN 5305-01-274-8613

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-274-8613

| Thread Class:                         |
|---------------------------------------|
| 3a                                    |
| Thread Direction:                     |
| Right-hand                            |
| Thread Length:                        |
| 0.240 inches                          |
| Fastener Length:                      |
| Between 0.845 inches and 0.875 inches |
| Head Style:                           |
| Flat countersunk                      |
| Head Diameter:                        |
| Between 0.480 inches and 0.530 inches |
| Internal Drive Style:                 |
| Hexagon                               |
| Thread Diameter:                      |
| 0.250 inches                          |
| Grip Length:                          |
| 0.162 inches                          |
| Width Across Flats:                   |
| 0.156 inches                          |
| Thready Qty Per Inch (tpi):           |
| 28                                    |
| Min. Tensile Strength (psi):          |
| 160000 pounds per square inch         |
| Hardness Rating:                      |
| 36.0 rockwell c and 45.0 rockwell c   |
| Countersink Angle:                    |
| Between 80.0 degrees and 84.0 degrees |
| Material:                             |
| Stainless steel                       |
| Surface Treatment:                    |
| Oxide                                 |
| Thread Series Designator:             |
| Unf                                   |
| Shelf Life:                           |
| N/a                                   |
| Unit Of Measure:                      |
|                                       |
| Demilitarization:                     |
| No                                    |
| Fiig:                                 |
| A003b0                                |
|                                       |