NSN 5305-01-275-1188

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-275-1188

| View Online at https://aerobasegroup.com/nsn/5305-01-275-1188 |
|-----------------------------------------------------------------------|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.203 inches |
| Fastener Length: |
| Between 0.525 inches and 0.545 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| 0.317 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Material Accommodated Thickness: |
| Between 0.075 inches and 0.089 inches |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 304 stand-off |
| Material Specification: |
| Mil-s-23195 military specification single material response stand-off |
| Surface Treatment: |
| Passivate stand-off |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response stand-off |
| Thread Series Designator: |
| |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Demilitarization: |
| No |
| |
| |
| A003b0 |

NSN 5305-01-275-1188

Panel Screw Assembly - Page 2 of 2

Mil-std (military Standard):

Mil-s-23195 spec.

