

View Online at <https://aerobasegroup.com/nsn/5305-01-275-3245>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.245 inches and 0.255 inches

Fastener Length:

1.125 inches

Head Style:

Knurled no. 1

Head Diameter:

Between 0.495 inches and 0.505 inches

Head Height:

Between 0.172 inches and 0.204 inches

Point Length:

Between 0.115 inches and 0.135 inches

Point Diameter:

Between 0.125 inches and 0.135 inches

First Diameter From Head:

Between 0.125 inches and 0.135 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.750 inches

Point Style:

Cone

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

1

Point Chamfer Angle:

Between 85.0 degrees and 95.0 degrees

Material:

Steel comp 203ez or steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma or steel comp 303se

Material Specification:

Mil-w-52263 military specification all material responses or astm a581 military specification all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072, e300 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-w-52263 spec.