NSN 5305-01-275-4539



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-275-4539 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.907 inches and 1.000 inches **Fastener Length:** Between 0.969 inches and 1.000 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.089 inches and 0.096 inches **Hole Diameter:** 0.046 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, class 4 military specification single treatment response **Head Hole Configuration Style:** Round Color: Black **Thread Series Designator:**

Shelf Life: N/a

Unc

NSN 5305-01-275-4539

Machine Screw - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.