

View Online at <https://aerobasegroup.com/nsn/5305-01-275-6795>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.792 inches and 0.894 inches

**Fastener Length:**

Between 0.969 inches and 1.000 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.442 inches and 0.507 inches

**Internal Drive Style:**

Torque set

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

Between 24.0 rockwell c and 35.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Iron alloy 660

**Screw Material Specification:**

Ams 5737 assn standard single material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1102 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0