## NSN 5305-01-275-6806

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-275-6806

80205-nas7803 professional/industrial association standard

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.298 inches and 0.348 inches
Fastener Length:
Between 0.808 inches and 0.838 inches
Head Style:
Pan
Head Diameter:
Between 0.357 inches and 0.373 inches
Head Height:
Between 0.122 inches and 0.133 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

## NSN 5305-01-275-6806

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0