## NSN 5305-01-276-7464

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-276-7464 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.150 inches and 0.350 inches **Fastener Length:** Between 0.797 inches and 0.829 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.523 inches and 0.543 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 203ez **Material Specification:** Astm a581 ty xm-1 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-276-7464

Externally Relieved Body Screw - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.