

View Online at <https://aerobasegroup.com/nsn/5305-01-276-7470>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.355 inches and 0.437 inches

**Fastener Length:**

Between 0.417 inches and 0.437 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Color:**

Black fastener

**Material:**

Steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 309 fastener or steel comp 310 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 322 fastener or steel comp 324 fastener or steel comp 347 fastener or steel comp 302 fastener or steel comp 303cu fastener or steel comp 302b fastener or steel comp 303ma fastener or steel comp 303 fastener or steel comp 303 plus x fastener or steel comp 303se fastener or steel comp 384 fastener

**Surface Treatment:**

Oxide fastener

**Surface Treatment Specification:**

Mil-c-13924 cl4 military specification single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

**Mil-std (military Standard):**

Mil-c-13924 spec.