## NSN 5305-01-276-9198

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-276-9198 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.526 inches and 0.546 inches **Fastener Length:** Between 1.651 inches and 1.671 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.454 inches and 0.508 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.115 inches and 1.135 inches Width Across Flats: Between 0.1565 inches and 0.1587 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5305-01-276-9198

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0