NSN 5305-01-277-4344

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-277-4344
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.569 inches and 0.619 inches
Fastener Length:
Between 1.204 inches and 1.234 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.722 inches and 0.740 inches
Head Height:
Between 0.206 inches and 0.220 inches
Grip Diameter:
Between 0.3740 inches and 0.3745 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.375 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1578 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-277-4344

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0