NSN 5305-01-277-7317

Thread Class:

Thread Direction:

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-277-7317

Thread Direction.
Right-hand
Thread Length:
Between 0.845 inches and 1.000 inches
Fastener Length:
Between 0.970 inches and 1.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.3125 inches and 0.3160 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Surface Finish:
63.0 microinches bearing surface of head
Material:
Steel fastener
Material Specification:
Sae j429 assn standard single material response fastener
Surface Treatment:
Oxide fastener
Surface Treatment Specification:
Mil-c-13924 military specification single treatment response fastener
Thread Series Designator:
Unrc

NSN 5305-01-277-7317

Socket Head Cap Screw - Page 2 of 2



Specification Data:
80205-nas1352 professional/indus

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.