Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-277-7884

Inre	ad Class:
3a	
Thre	ad Direction:
Right	t-hand
Thre	ad Length:
0.875	5 inches
Fast	ener Length:
Betw	een 0.970 inches and 1.000 inches
Head	d Style:
Flat o	chamfer
Head	d Diameter:
Betw	een 0.303 inches and 0.312 inches
Head	I Height:
Betw	een 0.185 inches and 0.190 inches
Lock	ting Feature:
Strip	threads
Inter	nal Drive Style:
Hexa	igon
Thre	ad Diameter:
0.190) inches
Widt	h Across Flats:
Betw	een 0.156 inches and 0.159 inches
Thre	ady Qty Per Inch (tpi):
24	
Min.	Tensile Strength (psi):
8000	0 pounds per square inch
Hard	ness Rating:
80.0	rockwell b fastener
Miniı	mum Yield Strength:
3000	0 pounds per square inch
Mate	rial:
Steel	comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or
steel	comp xm-7 fastener
Mate	rial Specification:
Astm	a493 assn standard all material responses fastener
Surfa	ace Treatment:
Pass	ivate fastener
Surfa	ace Treatment Specification:
Astm	a380 assn standard single treatment response fastener
Thre	ad Series Designator:
Unrc	
Spec	ification Data:
0020	5-nas1352 professional/industrial association standard

NSN 5305-01-277-7884

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

