NSN 5305-01-278-1961

Thread Direction:

Right-hand

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-278-1961

3					
Thread Length:					
Between 4.9 millimeters and 5.1 millimeters					
Fastener Length:					
Between 11.8 millimeters and 12.1 millimeters					
Head Style:					
Flat chamfer					
Head Diameter:					
Between 5.5 millimeters and 5.8 millimeters					
Head Height:					
Between 1.65 millimeters and 1.90 millimeters					
First Diameter From Head:					
Between 2.10 millimeters and 2.18 millimeters					
Distance From Largest Bearing Surface Of Head To End Of First Diameter:					
Between 6.78 millimeters and 7.22 millimeters					
Point Style:					
Flat					
Internal Drive Style:					
Slot					
Thread Diameter:					
3.0 millimeters					
Hardness Rating:					
35.0 rockwell c and 45.0 rockwell c					
Thread Pitch In Millimeters:					
0.5					
External Thread Tolerance Class:					
6g					
Externally Relieved Body Diameter Quantity:					
1					
Color:					
Olive drab					
Material:					
Steel comp 416					
Material Specification:					
Astm a582 cond a assn standard single material response					
Surface Treatment:					
Cadmium and chromate					
Surface Treatment Specification:					
Qq-p-416 type 2 cl 3 federal specification single treatment response					
Thread Series Designator:					
M					

NSN 5305-01-278-1961

Externally Relieved Body Screw - Page 2 of 2



_				
c	hο	.1+		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0