## NSN 5305-01-278-3789

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-278-3789



| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.319 inches and 0.431 inches  |
| Fastener Length:   |
| Between 2.079 inches and 2.109 inches  |
| Head Style:  |
| Fillister countersunk  |
| Head Diameter:   |
| Between 0.297 inches and 0.302 inches  |
| Head Height:   |
| 0.013 inches   |
| Grip Diameter:   |
| Between 0.1890 inches and 0.1895 inches  |
| Internal Drive Style:  |
| High-torque  |
| Thread Diameter:   |
| 0.190 inches   |
| Grip Length:   |
| Between 1.678 inches and 1.698 inches  |
| Features Provided:   |
| Cetyl alcohol lubricant  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 125000 pounds per square inch  |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Special Features:  |
| Screw supplied with min. Of 40 percent of non-bearing head surface coated with white paint color no. 37875 per fed-std-595 |
| Material:  |
| Steel comp xm-13   |
| Material Specification:  |
| Ams 5629 assn standard single material response  |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator   |

## Thread Series Designator:

Unjf

## NSN 5305-01-278-3789

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

