## NSN 5305-01-278-3789

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-278-3789

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.319 inches and 0.431 inches
Fastener Length:
Between 2.079 inches and 2.109 inches
Head Style:
Fillister countersunk
Head Diameter:
Between 0.297 inches and 0.302 inches
Head Height:
0.013 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 1.678 inches and 1.698 inches
Features Provided:
Cetyl alcohol lubricant
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Screw supplied with min. Of 40 percent of non-bearing head surface coated with white paint color no. 37875 per fed-std-595
Material:
Steel comp xm-13
Material Specification:
Ams 5629 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unjf

## NSN 5305-01-278-3789

Close Tolerance Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0