NSN 5305-01-278-5074

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-278-5074 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.395 inches **Fastener Length:** Between 0.980 inches and 1.010 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas 4006 assn standard 1st treatment response or ams 2506 assn standard 2nd treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

NSN 5305-01-278-5074

Close Tolerance Screw - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0