NSN 5305-01-278-9619

Unit Of Measure:

Externally Relieved Body Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-278-9619



Thread Class: 2a **Thread Direction:** Right-hand Thread Length: 0.090 inches **Fastener Length:** 0.292 inches **Head Style:** Flat chamfer **Head Diameter:** 0.145 inches **Head Height:** Between 0.070 inches and 0.085 inches **First Diameter From Head:** Between 0.051 inches and 0.063 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.080 inches and 0.089 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Min shank diameter 0.082, max diameter 0.088 Material: Steel comp 303 or steel comp 416 **Material Specification:** Astm a582 cond a assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 1 federal specification single treatment response or qq-p-35 type 2 federal specification single treatment response or qq-p-35 type 3 federal specification single treatment response or qq-p-35 type 4 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

NSN 5305-01-278-9619

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0