Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-278-9619

Inread	Class:
2a	
Thread	Direction:
Right-ha	and
Thread	Length:
0.090 in	nches
Fasten	er Length:
0.292 in	nches
Head S	tyle:
Flat cha	amfer
Head D	iameter:
0.145 in	nches
Head H	leight:
Betwee	n 0.070 inches and 0.085 inches
First Di	iameter From Head:
Betwee	n 0.051 inches and 0.063 inches
Distanc	ce From Largest Bearing Surface Of Head To End Of First Diameter:
Betwee	n 0.080 inches and 0.089 inches
Interna	I Drive Style:
Slot	
Thread	Diameter:
0.086 in	nches
Thread	y Qty Per Inch (tpi):
56	
Externa	ally Relieved Body Diameter Quantity:
1	
Special	I Features:
Min sha	ank diameter 0.082, max diameter 0.088
Materia	al:
Steel co	omp 303 or steel comp 416
Materia	Il Specification:
Astm at	582 cond a assn standard all material responses
Surface	e Treatment:
Passiva	ate
Surface	e Treatment Specification:
Qq-p-3	5 type 1 federal specification single treatment response or qq-p-35 type 2 federal specification single treatment response or qq-p-35
type 3	federal specification single treatment response or qq-p-35 type 4 federal specification single treatment response
Thread	Series Designator:
Unc	
Shelf L	ife:
N/a	
Unit Of	Measure:

Externally Relieved Body Screw - Page 2 of 2

AeroBase Group

Demilitarization:

No

Fiig:

A003b0