NSN 5305-01-278-9626

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-278-9626 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 0.386 inches and 0.416 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.322 inches and 0.387 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 24.0 rockwell c and 35.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1623 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-278-9626

Machine Screw - Page 2 of 2



Fiig:

A500d0