

View Online at <https://aerobasegroup.com/nsn/5305-01-278-9637>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.880 inches and 0.947 inches

**Fastener Length:**

Between 2.140 inches and 2.187 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 1.135 inches and 1.145 inches

**Grip Diameter:**

Between 0.5607 inches and 0.5616 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.562 inches

**Grip Length:**

1.250 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Countersink Angle:**

100.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas339 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0