

View Online at <https://aerobasegroup.com/nsn/5305-01-278-9639>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.141 inches and 0.171 inches

Fastener Length:

0.578 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.190 inches and 0.198 inches

Head Height:

0.112 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.112 inches

Width Across Flats:

0.094 inches

Thready Qty Per Inch (tpi):

40

Min. Tensile Strength (psi):

140000 pounds per square inch

Material:

Steel comp 301 stand-off or steel comp 302 stand-off or steel comp 302b stand-off or steel comp 303 stand-off or steel comp 303se stand-off or steel comp 304 stand-off or steel comp 304l stand-off or steel comp 305 stand-off or steel comp 308 stand-off or steel comp 309 stand-off or steel comp 309s stand-off or steel comp 310 stand-off or steel comp 310s stand-off or steel comp 314 stand-off or steel comp 316 stand-off or steel comp 316l stand-off or steel comp 317 stand-off or steel comp 321 stand-off or steel comp 347 stand-off or steel comp 348 stand-off or steel comp 384 stand-off or steel comp 385 stand-off

Material Specification:

Ams 5737 assn standard single material response fastener

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: