## NSN 5305-01-279-0466

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-279-0466 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.245 inches and 0.375 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.3750 inches and 0.3790 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b Material: Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp 302 or steel comp xm-7 **Material Specification:** Astm a493 assn standard all material responses **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416 type 1 cl 2 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-279-0466

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0